

STG01 - CO,

The STG Controllers are an easy way to automate ventilation systems and promote thermal comfort and air quality for your business.

The products feature temperature, humidity, carbon monoxide, carbon dioxide, volatile organic Compounds and fine particulate matter sensors, with the possibility of customization according to the project and software personalization for your application.

They are precise in variable control, easy to install, and can be easily accessed through their WI-FI interface, or the STG-IHM Touch Screen, offering both analog (0-10V) and digital outputs for each parameter.

SPECIFICATIONS STGOI - CO₂ 130.02

SOLD SEPARATELY. COMPATIBLE

WITH ALL STG CONTROLLERS.

DESCRIPTION CORRESPONDENCE

POSSIBILITIES.

MODEL	STG01 - CO ₂
MONITORED VARIABLE(S)	CARBON DIOXIDE
MEASUREMENT RANGE	400 ~ 8192 PPM
POWER SUPPLY VOLTAGE	24 VDC

POWER SUPPLY TYPE WALL CHARGER (P4 JACK CONNECTOR) OR SWITCHED POWER SUPPLY (CONNECTION VIA 1.5 MM² CABLES)

01 ANALOG OUTPUT	0 ~ 10 VDC
RELAY OUTPUT	NO + NC
CURRENT SUPPORTED BY THE RELAY	10 A (120 Vac) OR 7 A (240 Vac)
WEB INTERFACE FROM OWN WIFI ACCESS POINT	YES
WIRELESS COMMUNICATION WITH OTHER STG UNITS	YES (CUSTOMIZATION OPTION)
STORAGE TEMPERATURE	6 A 40° C

EXPLORE OTHER AVAILABLE PARAMETERS AND CUSTOMIZATION