

CONTROLLER STG02 - AHU CO₂

The STG Controllers are an easy way to automate ventilation systems and promote thermal comfort and air quality for your business.

The products feature temperature, humidity, carbon monoxide, carbon dioxide, volatile organic Compounds and fine particulate matter sensors, with the possibility of customization according to the project and software personalization for your application.

They are precise in variable control, easy to install, and can be easily accessed through their WI-FI interface, or the STG-IHM Touch Screen, offering both analog (0-10V) and digital outputs for each parameter.



DESCRIPTION

CORRESPONDENCE

MODEL	CARBON DIOXIDE CONTROLLER WITH WIFI INTERFA	CE.	
MEASUREMENT RANGE	CO2 = 400 ~ 8192 PPM		
01 ANALOG INPUT	0 - 10V	ODUCT WITH	
03 ANALOG OUTPUTS	0 - 10V	A STATE OF THE STA	
MODBUS RS485 COMMUNICATION		JANECT, SHRING	
01 DRY CONTACT RELAY OUTPUT	NO/NC	Stg ⁰²	
01 SOLID-STATE RELAY OUTPUT		Torreporature Humidity CO.	
POWER SUPPLY	24VDC	23.91 89.16 817 arr.25.00 arr.25.00 arr.25.00 arr.25.00 arr.2000 arr.25.00	
DASHBOARDS, GRAPHS, AND FIELDS FOR SETPOINT	INSERTION VIA WIFI INTERFACE.	SEE A CO ME STORE OF THE SEE ASSESSMENT OF THE SEC ASSESSMENT OF T	