

STG02-AHU

CO<sub>2</sub>, Temperature and Humidity

Air Quality Control



**storge** 

CO<sub>2</sub>

453 ppm

STG02 - AHU D CONTROLLER

## CONTROLLER STG02 - AHU D

The STG Controllers are an easy way to automate ventilation systems and promote thermal comfort and air quality for your business.

The products feature temperature, humidity, carbon monoxide, carbon dioxide, volatile organic Compounds and fine particulate matter sensors, with the possibility of customization according to the project and software personalization for your application.

They are precise in variable control, easy to install, and can be easily accessed through their WI-FI interface, or the STG-IHM Touch Screen, offering both analog (0-10V) and digital outputs for each parameter.

## SPECIFICATIONS STG02 - AHU D 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8 155.8

SOLD SEPARATELY. COMPATIBLE

WITH ALL STG CONTROLLERS.

## **DESCRIPTION**

## **CORRESPONDENCE**

**EXPLORE OTHER AVAILABLE PARAMETERS AND CUSTOMIZATION** 

POSSIBILITIES.

	***************************************		
MODEL	CARBON DIOXIDE, TEMPERATURE, HU CONTROLLER WITH WIFI INTERFACE.	CARBON DIOXIDE, TEMPERATURE, HUMIDITY AND DIFFERENTIAL PRESSURE CONTROLLER WITH WIFI INTERFACE.	
MEASUREMENT RANGE	CO2 = 400~ 8192 PPM, T = 6 ~ 40°C, U = 0 0-2000 / 0-5000 PA	CO2 = 400~ 8192 PPM, T = 6 ~ 40°C, U = 0 ~ 100%, PRESSÃO = 0-500 / 0-1000 / 0-2000 / 0-5000 PA	
01 ANALOG INPUT	0 - 10V	YRODUCT WITH WILL	
03 ANALOG OUTPUTS	0 - 10V		
MODBUS RS485 COMMUNICATION		· Name of the state of the stat	
01 DRY CONTACT RELAY OUTPUT	NO/NC	Stgor S336% Win HIM LONGOOD	
POWER SUPPLY	24VDC	23.91 89.16 817  serv.200 serv.800 serv.800	
DASHBOARDS, GRAPHS, AND FIELDS FOR SET	POINT INSERTION VIA WIFI INTERFACE.	Storage Storage	
		₩ 3	